

The RST-FLARE algorithm for gas flaring characterization by satellite data: the case of Niger Delta region



Mariapia Faruolo ^(1,*), Teodosio Lacava ⁽¹⁾, Nicola Pergola ⁽¹⁾, Valerio Tramutoli ⁽²⁾

* mariapia.faruolo@imaa.cnr.it

(1) Institute of Methodologies for Environmental Analysis, National Research Council (Italy)



2) School of Engineering, University of Basilicata (Italy)



EGU General Assembly 2019 Vienna | Austria | 8 April 2019




THE GAS FLARING

The burning of natural gas associated with oil extraction mainly acting as safety device to protect vessels/pipes from overpressuring due to unplanned upsets






A GLOBAL CHALLENGE





A GLOBAL CHALLENGE


Waste of a valuable
clean energy
resource



waste of 3,000MW of
electricity

DOUBLE
NEGATIVE
EFFECT

Anthropogenic
source of GHGs



~ 400 million tons of CO₂
into the atmosphere






THE ROLE OF REMOTE SENSING IN GF MONITORING

The **main issue** involved in addressing environmental aspects of flaring consists in the **lack of systematic, complete and reliable data** on its magnitude and spatial distribution

Limiting factors:

- (i) a limited access to official information on flaring locations
- (ii) the heterogeneity in spatial and temporal sampling strategies
- (iii) data typically self-reported by the flare operators


EXPLOITATION OF SATELLITE DATA






GENERAL GAS FLARES CHARACTERISTICS

- PERMANENT POINT-SOURCES
- SUB-PIXEL SOURCES
(fraction of 1×10^{-4} within a 1×1 km² pixel)



Planck curves for typical industrial processes and gas flaring temperatures, together with **SLSTR** SWIR (S5 and S6), MIR (S7 and F1) and TIR (S8, S9 and F2) channels [source: Caseiro et al. 2018]



Temperature histogram for 3 July 2013 VIIRS image
[source: Elvidge et al. 2013]

- MOSTLY CONTINUOUSLY ACTIVE
- HIGH TEMPERATURE





THE RST-FLARE ALGORITHM


1. DATA PRE-PROCESSING

2. FLARING SITES DETECTION

3. SOURCE EMISSIVE POWER COMPUTATION



4. GAS FLARED VOLUMES ESTIMATION

Faruolo, M.; Lacava, T.; Pergola, N.; Tramutoli, V. On the Potential of the RST-FLARE Algorithm for Gas Flaring Characterization from Space. *Sensors* 2018, 18(8), 2466, <https://doi.org/10.3390/s18082466>.






THE REGION OF INTEREST




THE NIGER DELTA REGION



THE ROBUST SATELLITE TECHNIQUES

[Tramutoli 1998, 2005, 2007]

Change detection scheme based on the **analysis of multiyear series of satellite data** acquired in **homogenous spatiotemporal conditions** to reconstruct the normal behavior of the signal (i.e., same spectral channel, same geographic area, same month and hour of acquisition)



V : signal measured at time t for each pixel (x, y)

The signal behavior in “normal” conditions expressed in terms of

V_{REF} = monthly temporal mean
 σ_v = standard deviation



THE ROBUST SATELLITE TECHNIQUES

[Tramutoli 1998, 2005, 2007]

ALICE

Absolutely Local Index of Change of the Environment

iii.

$$\otimes_V(x, y, t) \equiv \frac{V(x, y, t) - \mu_V(x, y)}{\sigma_V(x, y)}$$

standardized variable characterized by a Gaussian behavior

A pixel is flagged as “anomalous” when the deviation from the value expected to measure in normal conditions (μ) is greater than its natural variability (σ)



$$\otimes_V(x, y, \tau) > c$$

c = confidence level



THE ROBUST SATELLITE TECHNIQUES

[Tramutoli 1998, 2005, 2007]

For gas flares:

$$\otimes_{20-31}(x, y, t) = \frac{BT_{20-31}(x, y, t) - \mu_{20-31}(x, y)}{\sigma_{20-31}(x, y)} \geq 1.5$$

MIR: ch20 (3.66–3.84 μ m), TIR: ch31 (10.78–11.28 μ m)

implemented at the pixel level

assumed as representative of thermal anomalies related to gas flaring

Faruolo, M.; Coviello, I.; Filizzola, C.; Lacava, T.; Pergola, N.; Tramutoli, V. A satellite-based analysis of the Val d'Agri Oil Center (southern Italy) gas flaring emissions. *Nat. Hazards Earth Syst. Sci.*, 2014, 14, 2783-2793, DOI:10.5194/nhess-14-2783-2014, (<http://www.nat-hazards-earth-syst-sci.net/14/2783/2014/nhess-14-2783-2014.pdf>). ISSN: 1561-8633.



1. DATA PRE-PROCESSING

COLLECTED SATELLITE DATA

- Nighttime Daily Level 1B MODIS data (2000÷2016)
- NOAA CLASS web site archive
- BTs: **ch20** (3.66–3.84μm); **ch31** (10.78–11.28μm); **ch32** (11.77–12.27μm), at 1km spatial resolution

USED SATELLITE DATA

- **NO CLOUDY PIXELS**
(OCA approach on MODIS ch32)
- satellite zenith angle (**SATZA**) < 40°
(to reduce the impact of resampling and path radiance effects)
- solar zenith angle (**SOLZA**) < 101°
(to assure nighttime conditions)




2.


FLARING SITES DETECTION

I STEP: thermal anomalies detection

ALICE₂₀₋₃₁ time-series for Year_y



ALICE₂₀₋₃₁ Day_i



In each useful image (i.e., for all clear pixels with $\text{SatZA} < 40^\circ$ & $\text{SolZA} < 101^\circ$), a pixel is flagged as thermal anomaly if $\text{ALICE}_{20-31} \geq 1.5$




2.

FLARING SITES DETECTION


II.a STEP

A **time persistency criterion** applied to the $ALICE_{20-31} \geq 1.5$ for each year
(**Annual Aggregation**)


ALICE₂₀₋₃₁ time-series overlay



ALICE₂₀₋₃₁ frequency calculation



Flaring sites identification



Within each year, a pixel is classified as flaring site when thermal anomalies ($ALICE_{20-31} \geq 1.5$) are detected over **at least in 30% of images** belonging to the annual dataset (i.e., all clear pixels with $SatZA < 40^\circ$ & $SolZA < 101^\circ$)




2.

FLARING SITES DETECTION

ANNUAL ESTIMATES:
Flaring sites active «for sure» in that year

RESULT



Annual number of flaring sites detected in the Niger Delta region




2.

FLARING SITES DETECTION

II.b STEP

A **time persistency criterion** applied to the $ALICE_{20-31} \geq 1.5$ in all investigated years
(**Multi-temporal Aggregation**)

Annual flaring sites maps



«or» condition applied to the 17 annual maps

To take into account the activity variation of each site (due to decommissioning/reactivation periods, increasing in oil production, etc.), a multi-temporal map is defined assuming as **flaring sites** all those pixels that, **at least in one year within the 17 investigated**, have been detected as **anomalous**



2.


FLARING SITES DETECTION

RESULT

● VNF

[Elvidge et al 2013]

RST-FLARE



95% Match

MULTI-TEMPORAL MAP
Global and general overview of areas
affected by gas flaring activity in the
whole 17-year period

Background: SkyTruth layout (<https://viirs.skytruth.org/apps/heatmap/flar>)

3. SOURCE EMISSIVE POWER COMPUTATION

BRIGHTNESS TEMPERATURE EXCESS (BTE)

$$BTE_y = \sum_{j=1}^M \left(BT20_j - \langle BT20_{j,bg} \rangle \right) \cdot \alpha_{j,y} [K]$$

computed for each flaring site only when a thermal anomaly is identified by the ALICE₂₀₋₃₁

y refers to each of the investigated years in the 2000–2016 period

j refers to each of the M identified flaring site (only in presence of detected thermal anomaly)

BT20j is the brightness temperature (K) measured in the MODIS band 20 for the target j


<BT20j,bg>, referred to the background, is equal to the spatial mean of the temporal mean $\mu_{20}(x,y)$ in a 5x5 box around the site

α is a coefficient which weights the variability, between years, in sampling and cloud cover



3. SOURCE EMISSIVE POWER COMPUTATION

RESULT



Flaring sites BTE temporal trend



4. GAS FLARED VOLUMES ESTIMATION

LINEAR REGRESSION MODEL :

$$\text{Gas flared}_y = \gamma * \text{BTE}_y + \beta$$

Gas flared (assessed for the year y): the response variable in the model (Y)

BTE: the predictor variable (X)

γ and β : the regression coefficient and the Y-intercept (site-specific coefficients derived and valid for the Niger Delta)

OPEC: Organization of the Petroleum Exporting Countries

http://www.opec.org/opec_web/static_files_project/media/downloads/publications/ASB2016.pdf

EIA: Energy Information Administration

https://www.eia.gov/beta/international/analysis_includes/countries_long/Nigeria/nigeria.pdf



4. GAS FLARED VOLUMES ESTIMATION


RESULT

Source	Temporal Range	Regression Model Equation	R ²	<i>p</i> -Value	Year of Estimation	Gas Flared Volume [BCM]
OPEC	2000–2013	Gas flared [BCM] = 0.0005*BTE + 9.401	65%	<0.01	2014	14.3
					2015	12.4
					2016	11.9
EIA	2005–2013	Gas flared [BCM] = 0.0008*BTE + 3.902	67%	<0.01	2014	13.4
					2015	10.4
					2016	9.5



4. GAS FLARED VOLUMES ESTIMATION

RESULT




Annual values of gas flared volumes computed by RST-FLARE



4. GAS FLARED VOLUMES ESTIMATION

RESULT

RST-FLARE performances:




when compared to other two satellite products:

RST-FLARE (OPEC-based) vs MOVET: **R=62%** (2000-2013)

RST-FLARE (EIA-based) vs MOVET: **R=86%** (2005-2013)

RST-FLARE vs VNF: **R=95%** (2012-2016)



when compared to official data:

when referred to NNPC	Max Bias	Min Bias	Mean Bias
RST-FLARE OPEC-based	78.4%	0.3%	19.7%
RST-FLARE EIA-based	67.0%	0.8%	15.9%
MOVET	78.9%	3.2%	34.1%
VNF	42.5%	6.2%	24.9%



4. GAS FLARED VOLUMES ESTIMATION

RESULT

⇒ in the long period:

	NNPC	RST-FLARE (OPEC_based)	MOVET
2000-2013	270.7 BCM	246.7 BCM (-9%)	344.8 BCM (+27%)
	NNPC	RST-FLARE (EIA_based)	MOVET
2005-2013	154.9 BCM	158.2 BCM (+2%)	197.5 BCM (+34%)
	NNPC	RST-FLARE (OPEC-based) (EIA-based)	VNF
2012-2016	59.3 BCM	62.7 BCM (+6%) 68.8 BCM (+16%)	42.9 BCM (-28%)





CONCLUSION & WORK IN PROGRESS

RST-FLARE configuration, based on nighttime **MIR&TIR MODIS data**, demonstrated to be a reliable semi-automatic tool for

- i) *identifying gas flares*
- ii) *estimating gas flared volumes*
- iii) *analyzing possible spatiotemporal dynamics of flaring activity*

Works in progress are currently focused on the calibration of a new version of RST-FLARE aimed at exploiting the great potential of **NIR and SWIR bands** (acquired by new generation satellite sensors, like **Suomi-NPP-J1/VIIRS and Sentinel-3/SLSTR**) to further improve its performances in detecting flares and measuring their radiant power



Thank you for the attention



mariapia.faruolo@imaa.cnr.it