


Full-waveform inversion of Ground Penetrating Radar data for target characterization in multilayer environments


Alessandro Fedeli, Matteo Pastorino, and Andrea Randazzo

Department of Electrical, Electronic, Telecommunications Engineering, and Naval Architecture
University of Genoa, Italy




In this contribution, the full dielectric characterization of an underground region of interest is retrieved by a quantitative inversion approach that works in the mathematical framework of Lebesgue spaces with variable exponents [1]. The most important parameter of this algorithm is represented by the map of the exponent function inside the investigation domain [2]. Numerical results in a cross-borehole configuration are presented to check the effectiveness of the inversion approach.

Reconstructed relative dielectric permittivity



Map of the exponent function



Ground: $\epsilon_r = (4, 0.6)$; **Target:** \varnothing 0.2 m, $\epsilon_r = 1$; **Configuration:** multistatic cross-borehole, 22 meas. pts., 300 MHz

- [1] C. Estatico, A. Fedeli, M. Pastorino, and A. Randazzo, "Quantitative microwave imaging method in Lebesgue spaces with nonconstant exponents," *IEEE Transactions on Antennas and Propagation*, vol. 66, no. 12, pp. 7282–7294, Dec. 2018, doi: [10.1109/TAP.2018.2869201](https://doi.org/10.1109/TAP.2018.2869201).
- [2] C. Estatico, A. Fedeli, M. Pastorino, and A. Randazzo, "Microwave imaging by means of Lebesgue-space inversion: An overview," *Electronics*, vol. 8, no. 9, p. 945, Sep. 2019, doi: [10.3390/electronics8090945](https://doi.org/10.3390/electronics8090945).