

Effectiveness Analysis of Multi-purpose Dam : Socio-hydrology Modeling Approach


Sleemin Lee¹ and Doosun Kang^{2*}

(1) Master Student, Dept. of Civil Engineering, Kyung Hee University

(2) Professor, Dept. of Civil Engineering, Kyung Hee University

*) Corresponding Author: Kyung Hee University, Yongin-si, Gyeonggi-do 17104, Rep. of Korea

Introduction



Keywords: Climate change, Multi-purpose dam, Socio-hydrology


- Additionally, climate change and socio-economic scenarios were applied to analyze the future effects of the multi-purpose dam on the population change, regional economy, water supply, and flood damage prevention of the target area.

METHODOLOGY


- Identify target area and target facility
 - Collect historical data of social and hydrological components of the target area
 - Identify the causal relationship between components using the causal loop diagram
 - Estimate the relational formulas between components based on their causal relationships
 - Construct the socio-hydrology model using a system dynamics technique
 - Develop future scenarios (e.g., climate change, socio-economic)
 - Run model and analyze the simulation results
- Flow chart of study

Flow chart of study

Causal Loop of Socio-Hydrology Model



Study Area




Location of Hoengseong multi-purpose dam

- Location
Gangwon-do, South Korea
 - Dam construction period
1993/12 – 2000/11
 - Dam operation starts at 2002
 - Hoengseong-dam specification
- | Parameter | Value |
|---------------------|-----------------------------|
| Length | 205.0 m |
| Height | 48.5 m |
| Basin area | 209 km ² |
| Total water storage | 86.9 million m ³ |

- Components of Socio-Hydrology model

Socio-sectors		Hydro-sectors
Population	Flooding area	Domestic, Industrial, and agricultural water demand
Land use	Flood/drought damage	
Gross Regional Domestic Product	Water supply rate	Dam operation
		Annual rainfall
		River maintenance flow


- Dam operation



RESULTS


① Scenario 1 – w/ and w/o DAM

- Population in 2045
: 460,000 (With DAM), 380,000 (Without DAM)




Population comparison between With DAM & Without DAM

- GRDP(Gross Regional Domestic Product) in 2045
: 12 trillion won (With DAM), 8 trillion won (Without DAM)



GRDP comparison between With DAM & Without DAM


- Total Flooding area
: 15ha (With DAM), 4,500ha (Without DAM)
» Flood Damage is approximately 90 billion won



Flooding area comparison between With DAM & Without DAM


② Scenario 2 - Extreme climate change

- Water supply rate(30yr avg.)
: 0.95 (S1), 0.91 (S2)
→ S2 reduced by approximately 4% due to extreme droughts.



Comparison of S1 and S2 for Water supply rate


- GRDP in 2045
: 12 trillion won(S1), 11 trillion won(S2)
→ Resulting in a difference of approximately 1 trillion won



Comparison of S1 and S2 for GRDP

③ Scenario 3 – Urbanization/Industrialization


- Assumptions
1) Higher-than-expected birth
2) Increase in water consumption
3) Increase in production per unit of industrial land



Comparison of S1 and S3 for Annual water demand

- Increased GRDP → Population influx → Soar demand for living and industrial water

- Total water use in 2045
: 78 million m³ (S1), 95 million m³ (S3)
- Water supply rate(30yr avg.)
: 0.95(S1), 0.81(S3)



Comparison of S1 and S3 for Water supply rate

CONCLUSION

- Results summary

- Sce. 1 – By constructing the dam, the downstream society receives positive impact of population, GRDP, flood prevention, water supply
- Sce. 2 – The massive damage caused by extreme climate change will not occur in the area with proper dam operation. GRDP and population are expected to increase consistently
- Sce. 3 – The water consumption continuously increases due to urbanization and economic revitalization. The average water supply rate of Sce. 3 is expected to be approximately 0.81, which is significantly lower than that of Sce. 1
- The developed socio-hydrology model can be used as a decision-making tool to policymakers who are planning the construction of new multi-purpose dams. It can also be applied to the effectiveness analysis and planning of other water resource facilities.

Acknowledgement

This study is supported by Korea Ministry of Environment (MOE) as “Graduate School specialized in Climate Change”