

Faulted geological contacts: constraining uncertainty of discontinuities orientation using triangulation and combinatorial algorithm

M. Michalak¹, R. Kuzak¹, P. Gładki², and A. Kulawik²

University of Silesia in Katowice, Poland

¹ Faculty of Natural Sciences, Institute of Earth Sciences in Sosnowiec

² Faculty of Science and Technology

1 Introduction


2 Results

3 Summary



Problem

We'd like to create a simple geological model on a faulted contact using three-point method and triangulation. But we don't know the extent to which this combination of methods is capable of representing faults...



Related approach

In fact we are developing an approach that has been already described: <https://doi.org/10.1016/j.cageo.2019.104322>



Using Delaunay triangulation and cluster analysis to determine the orientation of a sub-horizontal and noise including contact in Kraków-Silesian Homocline, Poland



Michał P. Michalak^{A,*}, Waldemar Bardziński^{B,2}, Lesław Teper^{A,3}, Zbigniew Małolepszy^{C,4}

^A Department of Applied Geology, Faculty of Earth Sciences, University of Silesia in Katowice, Bedzinska 60, 41-205, Katowice, Poland

^B Department of Fundamental Geology, Faculty of Earth Sciences, University of Silesia in Katowice, Bedzinska 60, 41-205, Katowice, Poland

^C Polish Geological Institute, National Research Institute Upper Silesian Branch, Krakowski czolg 1, 41-200, Katowice, Poland

Brief introduction to results

To address this issue, we created two synthetic models of faulted contacts: 1) vertical and 2) dipping at 60° to west.


Due to limited space of this presentation, we will focus on the second model.

We mainly ask:

- 1) can we accurately calculate the orientation of a discontinuity using three-point method and triangulation?
- 2) can combinatorial algorithm be useful in better constraining the discontinuity orientation?
- 3) can the distributions be modeled using circular von Mises distribution?


Variability of dip direction

This is a faulted contact dipping at 60° to west. Therefore, its expected dip direction is 270° .




Variability of dip direction

This is a distribution of orientations associated with the previously presented triangulated model (B). It seems that the concentration around the expected orientation (270°) is quite low...




Employing combinatorial algorithm

What about creating all possible triangles from the vertices given?
This is the result:



Surprising orientations

Weird but true...



Basic statistics

Mean direction for the triangulated model: 264.8151

Median direction fot the triangulated model: 262.875


Mean direction for the combinatorial model: 264.8618

Median direction fot the combinatorial model: 267.7852

We are not delighted but...

Statistics


- QQ-plots for the observations taken and statistical tests seem not to invalidate the hypotheses: 1) of 270° mean and 2) that orientations from **triangulated** models may be modeled using circular von Mises distributions



- statistical tests conducted for combinatorial approach do invalidate both the hypotheses: 1) of 270° mean and 2) that orientations from **combinatorial** approach may be modeled using circular von Mises distributions

Conducting spatial clustering

Let's conduct spatial clustering using three different approaches:



Conclusion

- The three-point approach in a faulted area must be used with caution as it can give **counterintuitive** dip directions for triangles cutting a fault.

Conclusion

- The three-point approach in a faulted area must be used with caution as it can give **counterintuitive** dip directions for triangles cutting a fault.
- While intrinsically incapable of calculating the fault dip angle, the three-point approach can also be adjusted to constrain the variability of the fault **strike**. It does not have the potential however of indicating the dip direction but only the relative positions of hangingwall and footwall.

Conclusion

- The three-point approach in a faulted area must be used with caution as it can give **counterintuitive** dip directions for triangles cutting a fault.
- While intrinsically incapable of calculating the fault dip angle, the three-point approach can also be adjusted to constrain the variability of the fault **strike**. It does not have the potential however of indicating the dip direction but only the relative positions of hangingwall and footwall.
- The combinatorial algorithm of generating all three-element subsets from an n -element set may be used to better assess (at least visually) the **confidence interval** for the fault strike that can be further used for conducting spatial clustering.

Conclusion

- Equal values of dip directions obtained for different borehole configurations should be investigated in terms of a hidden geometrical rule underlying this effect

Conclusion

- Equal values of dip directions obtained for different borehole configurations should be investigated in terms of a **hidden geometrical rule** underlying this effect
- statistical tests conducted for the combinatorial approach pose a challenge. It could be possibly solved by selecting only triangles below a given collinearity limit

Conclusion

- Equal values of dip directions obtained for different borehole configurations should be investigated in terms of a **hidden geometrical rule** underlying this effect
- statistical tests conducted for the combinatorial approach pose a challenge. It could be possibly solved by selecting only triangles below a given collinearity limit
- The patterns obtained through the proposed maps are clearly sensitive to the selection of the points representing a triangle. Taking more points from its interior or making a regularized (**grid**) version could be a solution to this problem.

Thanks for your attention!