

Jeric Alcala and Ilya Timofeyev

University of Houston


Subgrid-scale parametrization of unresolved scales in forced Burgers equation using Generative Adversarial Networks (GAN)

Finite-Volume Discretization

$$\frac{d}{dt}u_i = \frac{F_{i+1/2} - F_{i-1/2}}{\Delta x} + \rho_i, \quad i \in \{1, \dots, N\}$$

Define Coarse Variables

“Box” filter: Average over n points



$$U_I = \frac{1}{n} \sum_{k=n(I-1)+1}^{nI} u_k, \quad \text{sub-grid: } y_i = u_i - U_{I(i)}$$

Equation for Coarse Variables

$$\frac{d}{dt}U_I = -\frac{F_{I+1/2}^{tot} - F_{I-1/2}^{tot}}{n\Delta x} + \rho^I, \quad F_{I+1/2}^{tot}(\mathbf{U}, \mathbf{y}) = \frac{1}{n} \sum_{i \in \text{Box } I} F_{i+1/2}$$

Flux Decomposition

$$F_{I+1/2}^{tot}(\mathbf{U}, \mathbf{y}) = F_{I+1/2}(\mathbf{U}) + G_{I+1/2}(\mathbf{U}, \mathbf{y})$$

Generative Adversarial Networks

Neural Networks Designed to reproduce arbitrary probability distributions

$$G_{I+1/2}(\mathbf{U}, \mathbf{y}) \sim \text{Conditional GAN } \tilde{G}_{I+1/2}(U_I, U_{I+1})$$


$\tilde{G}_{I+1/2}(U_I, U_{I+1})$: NN trained on the DNS data; can be used far outside of the training regime

Test Case: Forced Burgers Equation

$$\partial_t u + \frac{1}{2} \partial_x u^2 = \nu \partial_{xx} u + \rho \quad \text{SGS} = -\frac{1}{2} \partial_x (\overline{uu} - UU)$$

Compare Equilibrium Properties

Energy Spectra:




Advantages of GAN Parametrization

1. Accurately reproduces equilibrium properties of the DNS
2. Adequate Response to Increased Forcing (10-20%) (regression completely fails)
3. Robustness with respect to changes in the averaging window $n = 4, 8, 16$

Energy Spectra:

(20% increase in forcing; no re-training)



J. Alcala and I. Timofeyev, “”Subgrid-scale parametrization of unresolved scales in forced Burgers equation using Generative Adversarial Networks (GAN)”, [arxiv.org](https://arxiv.org/abs/2106.11881), under revision *TCFD* [2021]