

Detecting infiltration pathways by means of multi-method geophysical interpretation: an urban case study

Jakob Gallistl, Georg Bano, Ingrid Schlögel



ZAMG
Zentralanstalt für
Meteorologie und
Geodynamik

Objectives and setting

- Reported water infiltration into cellar rooms with 2 days delay after rainfall
- Cellars are old and any excessive soil moisture will weaken structural integrity
- Geophysical imaging to investigate possible water infiltration pathways


2



Geophysical imaging approach


- Combination of geophysical methods: mitigate effects of urban setting

3







- Low and high frequency ground penetration radar (GPR) measurements:
 - 80 and 160 MHz on street
 - 500 and 1000 MHz on cellar walls
- Electrical resistivity tomography (ERT):
 - Street: 72 electrodes with 1 m spacing
 - Cellar: 60 electrodes with 0.5 m spacing
- Seismic measurements collected with 24x 4.5 Hz geophones streamer with 2 m spacing:
 - Refraction seismic tomography (RST)
 - Multichannel analysis of surface waves (MASW)


Geophysical imaging approach



Results – Street: ERT, RST and MASW along profile Tuchlauben 1





Shearwave velocity [m/s]




Results – Street: ERT and GPR (160 MHz)

6





Results – Cellar and street: ERT




Results – Cellar: GPR

8




Interpretation: imaging infiltration pathways (1)



Interpretation: imaging infiltration pathways (2)

10



Conclusions

- Joint analysis of geophysical imaging results allowed the interpretation of possible infiltration pathways
- However, independent verification based on hydrological testing and drilling is still ongoing

11

