



Managing geomorphological drivers of river hazards in the rapidly aggrading Waiho River, Franz Josef / Waiaua, Aotearoa New Zealand








Rose Beagley, Tim Davies, Ian Fuller, Matthew Gardner, Mark Healey & Gary Williams

- Long-term aggradation trend
- Currently 0.2 m yr^{-1}




- LiDAR DoD
- Pulsed sediment delivery
- Recent storms & glacier retreat







500 m cross section




1500 m cross section






- Changes in sediment storage 2016-2024
- Consistent aggradation on Waiho Fan



- Avulsion into Tatare
- Infilling Tatare
- Full switch probable







LiDAR Datasets


	2016	2019	2023	2024	
Collection Date	June	16 April	8 June	31 January	31 July
Collected By	New Zealand Aerial Surveys Ltd	Waikato University	University of Canterbury		
Collection Method	Fixed wing aircraft	Helicopter			
Sensor	Optech Orion H300	Riegl VUX-1LR	Riegl VUX240		
Altitude	1190 – 2375 m	350 m	300 m		
No. checkpoint surveys	(Unknown)	97	298	1640	1643
Standard deviation of checkpoint/point-cloud difference	0.016 m	0.017 m	0.051 m	0.047 m	0.026 m
Average checkpoint/point-cloud difference	0.007 m	0.001 m	-0.006 m	0.003 m	-0.002 m
RMS error	(Unknown)	0.017 m	0.051 m	0.047 m	0.034 m

LiDAR uncertainty & Aol



Land Cover Class	Characteristic Vertical Uncertainty (m)
Grass	0.15
Exposed river gravels	0.13
Tall vegetation	0.30
Inundated areas (without correction)	0.50
Inundated areas (with section corrections, 2016 only)	0.25
Coastal water (January and July 2024)	0.75
Deep water (through the Tatare cut in January 2024)	1.00




Cross-section locations
& GCD budget cells
(historic sections)



LiDAR DoDs Jan 2024 to Jul 2024




LiDAR DoDs Jun 2016 to Jul 2024




Bed Level and volumetric changes Jan 2024 to Jul 2024

	Cross Section / Cells	Mean Bed Level (m)		Net volume (m ³)		Reach net volume change (m ³)
		Change	Error (m)	Change	Error (%)	
Upper Valley	XS0-XS1	1.53	0.21	171,000	14	765,000
	XS1-XS2	1.8	0.26	415,000	14	
	XS2-XS3	0.66	0.2	160,000	30	
	XS3-XS4	0.23	0.16	22,000	70	
	XS4-XS5	-0.04	0.2	-3,000	-510	
Transport Reach	XS5-XS6	0.66	0.25	31,000	38	-24,000
	XS6-XS7	-0.12	0.19	-6,000	-158	
	XS7-XS8	-1.07	0.34	-40,000	-32	
	XS8-XS9	-0.6	0.27	-11,000	-46	
	XS9-XS10	0.06	0.15	2,000	254	
Callery Confluence to End of Helipad Bank	XS10-XS11	-0.13	0.18	-5,000	-142	-27,000
	XS11-XS12	-0.36	0.19	-7,000	-52	
	XS12-XS13	-0.21	0.2	-7,000	-96	
	XS13-XS14	-0.07	0.18	-1,000	-248	
	XS14-XS15	-0.13	0.21	-6,000	-158	
End of Helipad Bank to Waiho Loop	XS15-XS16	0.25	0.19	14,000	76	1,000
	XS16-XS17	0.05	0.17	9,000	325	
	XS17-XS18	-0.05	0.16	-10,000	-303	
	XS18-XS19	-0.64	0.2	-58,000	-31	
	XS19-XS20	-0.27	0.17	-82,000	-63	
	XS20-XS21	0.21	0.14	59,000	64	
	XS21-XS22	0.22	0.15	68,000	68	
	XS22-XS23	0.02	0.15	3,000	629	



Bed Level and volumetric changes Jun 2016 to Jul 2024

	Cross Section / Cells	Mean Bed Level (m)		Net volume (m³)		Reach net volume change (m³)
		Change	Error (m)	Change	Error (%)	
Upper Valley	XS0-XS1	7.38	0.22	932,000	3	3,158,000
	XS1-XS2	5.19	0.2	1,264,000	4	
	XS2-XS3	2.63	0.2	893,000	8	
	XS3-XS4	1.06	0.2	185,000	19	
	XS4-XS5	-1.08	0.2	-116,000	-18	
Transport Reach	XS5-XS6	0.97	0.22	73,000	23	230,000
	XS6-XS7	-0.87	0.2	-75,000	-23	
	XS7-XS8	1.61	0.2	82,000	13	
	XS8-XS9	2.1	0.24	99,000	12	
	XS9-XS10	1.09	0.18	51,000	17	
Callery Confluence to End of Helipad Bank	XS10-XS11	-1.49	0.22	-106,000	-15	-122,000
	XS11-XS12	-2.33	0.19	-88,000	-8	
	XS12-XS13	0.32	0.15	17,000	47	
	XS13-XS14	0.85	0.15	26,000	18	
	XS14-XS15	0.54	0.15	29,000	27	
End of Helipad Bank to Waiho Loop	XS15-XS16	0.75	0.16	49,000	21	2,542,000
	XS16-XS17	0.92	0.18	218,000	19	
	XS17-XS18	1.19	0.19	438,000	16	
	XS18-XS19	1.1	0.18	192,000	16	
	XS19-XS20	0.67	0.16	395,000	24	
	XS20-XS21	1.05	0.17	673,000	16	
	XS21-XS22	0.99	0.19	578,000	19	
	XS22-XS23	0.94	0.19	307,000	21	




Monitoring site	Owner	Elevation	Data	Period
Waiho Rv at SH6	WCRC	146 m	Rainfall/Water level	2009 to current
Waiho Rv at Douglas Hut	NIWA	221 m	Rainfall	1983 to current



Douglas Hut Rainfall

GCD period	Approximate length	Average monthly total (mm)	Time above, at and below the long-term monthly means		
			Drier (%)	Normal (%)	Wetter (%)
2016 – 2019	3 years	497	38	14	49
2019 – 2023	4 years	646	32	15	53
2023 – Jan 2024	8 months	555	43	14	43
Jan – Jul 2024	6 months	463	50	17	33



Emerging management issues



Why did Council commission the report?

Ongoing threat of the Waiho River

Previous workshops in 2000 and 2016 held to develop long-term sustainable management options – outcomes did not gain traction

Since 2016, the situation has worsened:

Continued aggradation (build-up of gravel in the riverbed)

A major break out (avulsion) channel into the Tartare Stream to the north in 2023


Fundamental change in the behaviour of the river which will have serious consequences on surrounding infrastructure and ecological values

Government funding had been allocated for the South Side. This has been frozen until an acceptable plan formalised for the Waiho.

Miltons Bank


Toe Failure








Tatare Avulsion

2023







	Volume Erosion (million m ³)	+/- Error (million m ³)	Volume Deposition (million m ³)	+/- Error (million m ³)	Net Volume Difference (million m ³)
2019-23	0.51	±0.07	0.13	±0.03	-0.38
2023-Jan24	0.70	±0.09	0.42	±0.10	-0.28
Jan24-Jul24	0.41	±0.09	0.15	±0.06	-0.26




Long section - July 2024 main channel (0 - 2000 m)





Long section - July 2024 main channel (2000 - 3675 m)





Landfill risks – WDC and multiple private





Risk Assessment


	Asset / Area	Status Quo/Residual Risk			Improved/Residual Risk				
		Likelihood	Consequences	Risk	Scenario	Rough Order Costs (rounded to \$0.5 M)	Likelihood	Consequences	Risk
North	Tatare <i>avulsion</i>	Almost certain	Severe	Critical	Build	\$15 M+	Possible	Severe	High
	Havill's <i>stopbank</i> (without <i>avulsion</i>)	Likely	Moderate	High	Upgrade	\$5 M	Unlikely	Moderate	Medium
	55 kph Corner <i>stopbank</i>	Possible	Severe	High	Build	\$3 M	Unlikely	Severe	Medium
	Heliport <i>stopbank</i>	Possible	Extreme	Critical	Upgrade	\$0.5 M	Possible	Extreme	Critical
	Church <i>stopbank</i>	Possible	Extreme	Critical	Upgrade	\$0.5 M	Possible	Extreme	Critical
	SH6 Bridge upstream	Rare	Extreme	High	Upgrade	\$0.5 M	Rare	Extreme	High
	State Highway 6 Bridge	Possible	Extreme	Critical	Upgrade	\$5 M	Rare	Extreme	High
South	Glacier Road	Unlikely	Extreme	High	Upgrade	\$2 M	Rare	Extreme	High
	Waka Kotahi stopbanks (SH6 to Canavan's Knob)	Likely	Extreme	Critical	Upgrade	\$3 M	Unlikely	Extreme	High
					Build	\$3 M	Unlikely	Extreme	High
					Relax	\$100 M+	Certain	Insignificant	Low
	Rubbish Dump <i>stopbank</i> (Canavan's Knob to Rata Knoll)	Almost certain	Severe	Critical	Upgrade	\$5 - 15 M	Possible	Severe	High
					Relax	\$50 – 70 M	Certain	Insignificant	Low
	Milton's <i>stopbank</i>	Almost certain	Severe	Critical	Upgrade	\$2 M	Likely	Severe	Critical
					Build	\$5 M+	Possible	Severe	High
					Relax	\$30 – 50 M	Certain	Insignificant	Low
	Lower valley (downstream of Milton's)	Likely	Moderate	High	Upgrade	\$2 - 5 M	Possible	Moderate	Medium

Release to the south

Land River Sea Consulting – model results

All true left (southern) stopbanks removed

- 2023 DEM
- True right stopbanks shown by white lines
- SH6 shown by white dashed line
- Tatare and Docherty flows not included



Release to the south

Land River Sea Consulting – model results


Upgrading and/or building stopbanks would have significant initial and on-going costs while not significantly reducing the *risk* of failure over a ten-year period.

However, removing all of the stopbanks on the south side of the river will:

- Reduce the *risk* of *stopbank* failure.
- Reduce the number of assets exposed to the *flood hazard*.
- Provide the Waiho River with more surface area to deposit sediment (and hence decrease the rate of bed level rise).
- Increase the lifespan of the north stopbanks and reduce their *risk* of failure during *flood* events.
- Reduce the pressure on the overflow path on the north bank upstream of the SH6 Bridge.
- Reduce the pressure of the developing *avulsion* into the Tatare Stream.
- Reduce the impact of the *aggradation* and flooding that will follow an Alpine fault or other earthquake.


Waiho River 10-Year Plan

[illegible]



PARA FRAMEWORK

- **Protect** – Reduce the extent and/or frequency of the *hazard*.
- **Avoid** – Ensure new development and property and vulnerable assets are not exposed to the *hazard*.
- **Retreat** – Relocate existing people, property and assets from locations exposed to the *hazard*.
- **Accommodate** – Reduce the consequences of the *hazard*.




Five Critical Action Areas



1. Emergency Management

and contingency planning



2. Release to South

Commit to and initiate investigation and design



3. Interim Structural Measures

Current works and other key risk areas

“10-year holding work”



4. Risk Management Data & Equip.

Monitoring and modelling



Future Management of the Waiho River

This report has been compiled by the 2023 Waiho Technical Advisory Group upon the request of the West Coast Regional Council

5. Governance & Stakeholder Engagement

Structure and resourcing

1. Emergency Management & Contingency Planning

- Most likely outcome is failure and damage
- Flooding will not be like it was previously
- Enhanced flood risk comms and planning needed
- Contingency plans are needed for key assets (WDC ponds, roads, stopbanks, etc)




2. Release to South

- Secure commitment and funding, and action release to the south and all that entails
- 10-year programme - start now (staged)
- 30 dwellings, landfills, chemical storage, fuel, wastewater, dairy effluent, power, telecom, structures, roads, ...
- A lot of consultation
- Develop a staging plan




Undertake holding works along the southern stopbanks and Glacier Road to provide protection for the southern *floodplain* while preparatory works for the release are undertaken.



Upgrade stopbanks on the north side

Phase 2: remove
Milton's *stopbank* and
the unlined Rubbish
Dump *stopbank* on
the south side.




**Only true left (southern) stopbanks
downstream of Canavan's Knob
removed**


- 2023 DEM
- True right and upstream of Canavan's Knob true left stopbanks shown by white lines
- SH6 shown by white dashed line
- Tatare and Docherty flows not included




Phase 3: remove
lined Rubbish
Dump *stopbank*
on the south side.



Phase 4: ` Realignment
and construction of
SH6 to the south of the
Waiho River.



Phase 5: remove
the remaining
southern
stopbanks
between the SH6
bridge and
Canavan's Knob.



3. Interim Structural Measures

- Need to try to hold the line while release to south is progressed
- Work programme still being assessed – risk priority – includes:
 - Existing contract works
 - Milton's Bank
- Further assess avulsion to Tatare Stream



4. Risk Management Data and Equipment

- Update 2016 monitoring strategy
 - Flood warning, imagery, survey
- Hydraulic and geomorphic modelling of risks and options



5. Governance & Stakeholder Engagement

- Develop Business Plan
- Consultation / Engagement

Full acknowledgements to the Waiho Technical Advisory Group convened by West Coast Regional Council in 2023 and reports listed below



Rose Beagley

Geomorphologist / Water Resources Scientist, Land River Sea Consulting
BSc, MSc



Tim Davies

Retired Professor
University of Canterbury
BSc (Hons), MSc and PhD in Civil Engineering



Ian Fuller

Professor in Physical Geography, Massey University
BSc Hons Geography, PhD



Matthew Gardner

Principal Engineer, Land River Sea Consulting
BE(Nat Res), CMEngNZ, CPEng



Mark Healey

Principal Engineer - Rivers
WSP
ME(Nat Res), CMEngNZ, CPEng



Gary Williams

Water and Soil Engineer,
G&E Williams Consulting
BE (Hons), BSc (Physics), MCom (Hons), FEngNZ



Future Management of the Waiho River

This report has been compiled by the 2023
Waiho Technical Advisory Group upon the
request of the West Coast Regional Council

10 October 2023
R. Beagley, T. Davies, I. Fuller, M. Gardner, M.
Healey, and G. Williams.



WAIHO RIVER

Geomorphic Change Detection Analysis:

2019, 2023, and January
and July 2024

13 September 2024
Client: West Coast Regional Council
Report by: Rose Beagley
Land River Sea Consulting Limited
www.landriversea.com


Land River Sea
CONSULTING

 WEST COAST
REGIONAL COUNCIL