The Shade Availability Index A new quantitative scale to support the design of shaded sidewalks and walking paths

Or Aleksandrowicz, Naama Shapira, Michelle C. Levenson, Shachar Zur and David Pearlmutter











Habima Square, Tel Aviv-Yafo Designer: Dani Karavan Shade is a design feature

Lack of shade is a design failure

Shade Index (SI): describes on a scale of 0 to 1 the ratio between maximum incoming insolation and blocked insolation for a specific point or area

$$SI_p = 1 - \left(\frac{Insolation_p}{Insolation_r}\right)$$

Aleksandrowicz, Or, Shachar Zur, Yonatan Lebendiger, and Yoav Lerman. "Shade Maps for Prioritizing Municipal Microclimatic Action in Hot Climates: Learning from Tel Aviv-Yafo." Sustainable Cities and Society 53 (February 1, 2020): 101931.





Spring/Summer Shade Index

0.00 - 0.02

0.03 - 0.04

0.05 - 0.06

0.07 - 0.08

0.09 - 0.11

0.12 - 0.14

0.15 - 0.17

0.18 - 0.21

0.22 - 0.26

0.27 - 0.31

0.32 - 0.38 0.39 - 0.46

0.47 - 0.58

0.59 - 0.81

0.82 - 1.00

Petah Tikva Part of a spring/summer shade map

Mapping: Morel Weisthal and Or Aleksandrowicz



Guidelines for Applying Quantitative Shade Indicators in Urban Planning in Israel

Or Aleksandrowicz, Naama Shapira, Michelle Clark Levenson, Shachar Zur and David Pearlmutter


June 2025








MAP the urban shade hierarchy by using shade maps



PRIORITIZE intervention sites for shade intensification or shade preservation



DESIGN shading according to the Shade Availability Index

Shade quantification: what should we consider?

- Reference Space (What is the spatial unit of reference?)
- Reference Time
 (What is the time span during which shade matters the most?)
- Reference surface (Which surface should be shaded?)

A sidewalk

- 6 August=6 May, 08:00-17:00 (DST)
- The sidewalk's surface

Thermal Comfort of Shade?

Rabin Square, Tel Aviv, 14.7.2020

14:37 14:52 14:52



Air temperature: 29.16 °C Relative Humidity: 67% Wind Speed: 1.63 m/s Global Solar Radiation: 64 W/m²

MRT: 37.30 °C

Feels like (PET): 31.01 °C Feels like (UTCI): 32.33 °C



Air temperature: 29.40 °C Relative Humidity: 66% Wind Speed: 2.41 m/s Global Solar Radiation: 832 W/m²

MRT: 62.25 °C

Feels like (PET): 40.02 °C Feels like (UTCI): 37.56 °C



Air temperature: 29.49 °C Relative Humidity: 66% Wind Speed: 1.18 m/s Global Solar Radiation: 63 W/m²

MRT: 35.61 °C

Feels like (PET): 31.15 °C Feels like (UTCI): 32.57 °C



15:03

Air temperature: 29.26 °C Relative Humidity: 67% Wind Speed: 1.75 m/s Global Solar Radiation: 832 W/m²

MDT, FO OC °C

MRT: 58.06 °C


Feels like (PET): 39.48 °C Feels like (UTCI): 37.27 °C

Aleksandrowicz, Or, and David Pearlmutter. "The Significance of Shade Provision in Reducing Street-Level Summer Heat Stress in a Hot Mediterranean Climate." Landscape and Urban Planning 229 (January 2023): 104588.


How to quantify shade in detailed design?

The Shade Availability Index (SAI) describes, on a scale of 0 to 1, the ratio of daytime hours during a reference date (for example, 08:00-17:00 on 6 August) when a sidewalk is in a sufficient state of shading.

A sidewalk is in a sufficient state of shading when at least half of its area at a given moment is shaded.




Shading levels rated according to the Shade Availability Index (SAI)




Acceptable shading

SAI ≥ 0.5



Very good shading


SAI ≥ 0.7




Excellent shading

SAI ≥ 0.9


Parametric evaluation of the Shade Availability Index




Parametric evaluation of the Shade Availability Index



Kikayon 1.6: Grasshopper code for parametric outdoor shade calculation Or Aleksandrowicz, Ezra Ozery











Kikayon 1.6: Grasshopper code for parametric outdoor shade calculation Or Aleksandrowicz, Ezra Ozery






Sadeghipour Roudsari, M., Pak, M.: Ladybug: a parametric environmental plugin for Grasshopper to help designers create an environmentallyconscious design. In: BS2013: 13th International IBPSA Conference., Chambéry, France (2013).





Kikayon 1.6: Grasshopper code for parametric outdoor shade calculation Or Aleksandrowicz, Ezra Ozery







Rate of compliance with shading targets: Main streets

North-South Orientation

Design scenario (main street)	Planting distance between trees	Percentage of cases in which acceptable shading is achieved (shade availability index: 0.5)		cases in very good is ach (shade av	tage of n which d shading nieved vailability c: 0.7)	Percentage of cases in which excellent shading is achieved (shade availability index: 0.9)	
		Western sidewalk	Eastern sidewalk	Western sidewalk	Eastern sidewalk	Western sidewalk	Eastern sidewalk
Buildings only		55	56	7	7	0	0
Buildings and <i>Celtis</i> bungeana trees after 5 years of growth		66	65	14	13	0	0
Buildings and <i>Delonix</i> regia trees after 5 years of growth	10 m	70	68	19	18	0	0
Buildings and shade trees (<i>C. bungeana/D.</i> regia) trees after 10 years of growth		100	99	98	97	69	72
Buildings and <i>C.</i> bungeana trees after 5 years of growth		78	83	44	53	9	7
Buildings and <i>D. regia</i> trees after 5 years of growth	5 m	100	97	89	84	33	32
Buildings and shade trees (<i>C. bungeana/D.</i> regia) trees after 10 years of growth		100	100	100	100	99	95

Northeast-Southwest Orientation

Design scenario (main street)	Planting distance between trees	Percentage of cases in which acceptable shading is achieved (shade availability index: 0.5)		Percentage of cases in which very good shading is achieved (shade availability index: 0.7)		Percentage of cases in which excellent shading is achieved (shade availability index: 0.9)	
		South- western sidewalk	North- eastern sidewalk	South- western sidewalk	North- eastern sidewalk	South- western sidewalk	North- eastern sidewalk
Buildings only		10	59	0	7	0	0
Buildings and <i>Celtis</i> bungeana trees after 5 years of growth		25	69	2	15	0	0
Buildings and <i>Delonix</i> regia trees after 5 years of growth	10 m	34	73	3	19	0	0
Buildings and shade trees (<i>C. bungeana /D.</i> regia) trees after 10 years of growth		100	100	100	97	82	84
Buildings and C. bungeana trees after 5 years of growth		82	92	28	71	0	22
Buildings and <i>D. regia</i> trees after 5 years of growth	5 m	100	96	76	80	40	43
Buildings and shade trees (C. bungeana /D. regia) trees after 10 years of growth		100	100	100	95	99	96

East-West Orientation

Design scenario (main street)	Planting distance between trees	Percentage of cases in which acceptable shading is achieved (shade availability index: 0.5)		Percentage of cases in which very good shading is achieved (shade availability index: 0.7)		Percentage of cases in which excellent shading is achieved (shade availability index: 0.9)	
		Northern sidewalk	Southern sidewalk	Northern sidewalk	Southern sidewalk	Northern sidewalk	Southern sidewalk
Buildings only		0	31	0	7	0	0
Buildings and <i>Celtis</i> bungeana trees after 5 years of growth		0	44	0	32	0	4
Buildings and <i>Delonix</i> regia trees after 5 years of growth	10 m	0	51	0	41	0	16
Buildings and shade trees (<i>C. bungeana/D.</i> regia) trees after 10 years of growth		100	86	100	82	97	79
Buildings and <i>C.</i> bungeana trees after 5 years of growth		22	60	19	52	0	28
Buildings and <i>D. regia</i> trees after 5 years of growth	5 m	51	70	46	64	25	44
Buildings and shade trees (<i>C. bungeana/D.</i> regia) trees after 10 years of growth		100	94	100	93	97	88

Rate of compliance with shading targets: Side streets

North-South Orientation

Design scenario (side street)	Planting distance between trees	Percentage of cases in which acceptable shading is achieved (shade availability index: 0.5)		Percentage of cases in which very good shading is achieved (shade availability index: 0.7)		Percentage of cases in which excellent shading is achieved (shade availability index: 0.9)	
		Western sidewalk	Eastern sidewalk	Western sidewalk	Eastern sidewalk	Eastern sidewalk	Western sidewalk
Buildings only		89	92	53	59	0	10
Buildings and <i>Celtis</i> bungeana trees after 5 years of growth		98	94	70	77	16	25
Buildings and <i>Delonix</i> regia trees after 5 years of growth	10 m	99	95	73	82	19	41
Buildings and shade trees (<i>C. bungeana/D.</i> regia) trees after 10 years of growth		100	100	100	100	100	100
Buildings and <i>C.</i> bungeana trees after 5 years of growth		100	100	99	98	80	85
Buildings and <i>D. regia</i> trees after 5 years of growth	5 m	100	100	100	100	98	96
Buildings and shade trees (<i>C. bungeana/D.</i> regia) trees after 10 years of growth		100	100	100	100	100	100


Northeast-Southwest Orientation

Design scenario (side street)	Planting distance between trees	Percentage of cases in which acceptable shading is achieved (shade availability index: 0.5)		Percentage of cases in which very good shading is achieved (shade availability index: 0.7)		Percentage of cases in which excellent shading is achieved (shade availability index: 0.9)	
		South- western sidewalk	North- eastern sidewalk	South- western sidewalk	North- eastern sidewalk	South- western sidewalk	North- eastern sidewalk
Buildings only		70	93	30	65	0	9
Buildings and Celtis bungeana trees after 5 years of growth		81	96	47	77	0	24
Buildings and Delonix regia trees after 5 years of growth	10 m	89	100	66	95	23	73
Buildings and shade trees (<i>C.</i> bungeana/D. regia) trees after 10 years of growth		100	100	100	100	100	100
Buildings and C. bungeana trees after 5 years of growth		100	100	100	100	84	93
Buildings and <i>D.</i> regia trees after 5 years of growth	5 m	100	100	100	100	98	99
Buildings and shade trees (<i>C.</i> bungeana/ <i>D.</i> regia) trees after 10 years of growth		100	100	100	100	100	100

East-West Orientation


Design scenario (side street)	Planting distance between trees	Percentage of cases in which acceptable shading is achieved (shade availability index: 0.5)		Percentage of cases in which very good shading is achieved (shade availability index: 0.7)		Percentage of cases in which excellent shading is achieved (shade availability index: 0.9)	
		Northern sidewalk	Southern sidewalk	Northern sidewalk	Southern sidewalk	Northern sidewalk	Southern sidewalk
Buildings only		0	71	0	46	0	0
Buildings and Celtis bungeana trees after 5 years of growth		71	86	5	84	0	75
Buildings and Delonix regia trees after 5 years of growth	10 m	96	90	75	88	2	80
Buildings and shade trees (<i>C. bungeana/D. regia</i>) trees after 10 years of growth		100	100	100	100	100	99
Buildings and C. bungeana trees after 5 years of growth		100	93	100	92	100	84
Buildings and <i>D.</i> regia trees after 5 years of growth	5 m	100	98	100	96	100	94
Buildings and shade trees (<i>C.</i> bungeana/ <i>D.</i> regia) trees after 10 years of growth		100	100	100	100	100	100

How to design shade with the SAI? A real-life example





Source: Survey of Israel



Right-of-way Shade Index: 0.09

Road Shade Index: 0.04

Sidewalk 1 Shade Index: 0.18

Sidewalk 2 Shade Index: 0.06

Sidewalk 1 Shade Availability Index: 0.1 Sidewalk 2 Shade Availability Index: 0.0

Number of trees: 0

Trees per 1000 sqm: 0

Tree canopy cover ratio: 0

Baseline, no trees

Width of the southern sidewalk (1): 7.2 m


Width of the northern sidewalk (2): 3.9 m


Right-of-way width: 20.1 m

Street segment length: 160 m









Right-of-way Shade Index: 0.34

Road Shade Index: 0.28

Sidewalk 1 Shade Index: 0.34 Sidewalk 2 Shade Index: 0.49


Sidewalk 1 Shade Availability Index: 0.3 Sidewalk 2 Shade Availability Index: 0.6

Number of trees: 32


Trees per 1000 sqm: 10.08


Tree canopy cover ratio: 0.20

Adding 16 Delonix regia trees (10 m tree intervals), shading conditions after 5 years.



2





Right-of-way Shade Index: 0.37

Road Shade Index: 0.32


Sidewalk 1 Shade Index: 0.38 Sidewalk 2 Shade Index: 0.49


Sidewalk 1 Shade Availability Index: 0.4 Sidewalk 2 Shade Availability Index: 0.6

Number of trees: 36

Trees per 1000 sqm: 11.34 Tree canopy cover ratio: 0.22 Adding two additional Delonix regia trees to the southern sidewalk, shading conditions after 5 years.

Z





Right-of-way Shade Index: 0.43

Road Shade Index: 0.40

Sidewalk 1 Shade Index: 0.45 Sidewalk 2 Shade Index: 0.49

Sidewalk 1 Shade Availability Index: 0.4 Sidewalk 2 Shade Availability Index: 0.6


Number of trees: 46


Trees per 1000 sqm: 14.48

Tree canopy cover ratio: 0.28

Increasing the number of Delonix regia trees on the southern sidewalk to 30 (5 m tree intervals), shading conditions after 5 years.

2





Right-of-way Shade Index: 0.41

Road Shade Index: 0.21

Sidewalk 1 Shade Index: 0.64 Sidewalk 2 Shade Index: 0.49

Sidewalk 1 Shade Availability Index: 1.0 Sidewalk 2 Shade Availability Index: 0.6


Number of trees: 46


Trees per 1000 sqm: 14.48

Tree canopy cover ratio: 0.28

Moving the Delonix regia trees on the southern sidewalk 3.2 m from the curb, allowing for the integration of a bike lane, shading conditions after 5 years.

Z





Right-of-way Shade Index: 0.32

Road Shade Index: 0.17

Sidewalk 1 Shade Index: 0.46

Sidewalk 2 Shade Index: 0.49

Sidewalk 1 Shade Availability Index: 0.4

Sidewalk 2 Shade Availability Index: 0.6


Number of trees: 32

Trees per 1000 sqm: 10.08


Tree canopy cover ratio: 0.20


After moving the Delonix regia trees on the southern sidewalk 3.2 m from the curb, re-examine the shading conditions using only 16 trees, shading conditions after 5 years.











Right-of-way Shade Index: 0.34

Road Shade Index: 0.17


Sidewalk 1 Shade Index: 0.49 Sidewalk 2 Shade Index: 0.49


Sidewalk 1 Shade Availability Index: 0.5 Sidewalk 2 Shade Availability Index: 0.6

Number of trees: 34

Trees per 1000 sqm: 10.71 Tree canopy cover ratio: 0.21 Adding two additional trees on the southern sidewalk (18 in total) to achieve the minimum threshold on both sidewalks, shading conditions after 5 years.

2





Right-of-way Shade Index: 0.65

Road Shade Index: 0.48


Sidewalk 1 Shade Index: 0.79 Sidewalk 2 Shade Index: 0.84


Sidewalk 1 Shade Availability Index: 1.0 Sidewalk 2 Shade Availability Index: 1.0

Number of trees: 34


Trees per 1000 sqm: 10.71 Tree canopy cover ratio: 0.21 Calculating shading conditions after 10 years.

Z










After 5 years: Achieving acceptable shading on both sidewalks using 34 trees



After 10 years: Achieving the highest level of shading on both sidewalks without additional trees



Keep Cool!

Or Aleksandrowicz oraleks@technion.ac.il